

Dissolved Ozone Monitor

Data Logging Dissolved Ozone Monitor

This is a complete dissolved ozone monitoring system that includes a data-logger, dissolved Ozone sensor, sensor flow cell, and a pressure switch. This system can be used with clean, dirty, moving, or standing water.



Features

- Internal DataLogging
- Integrated Pressure Switch
- Selectable Range
- Reliable Performance

Product ID: **DO-363**
 Lead Time: **4 weeks**
 Price: **\$2,850.00**

Ozone Sensor

Replacement Sensor Probe

	Part Number	Description	Price	Add To Cart
44651	DO-363 Sensor	0 to 20 ppm Ozone Sensor	Online Pricing	Buy Online!

Calibration Kit

Dissolved Ozone Monitor must be calibrated on site and in your water. If you do not currently have an ozone test kit we recommend purchasing this colorimetric test kit:

	Part Number	Price	Buy Online
43649	K-7402	Online Pricing	Buy Online!

Specifications

Range:	0-1.999 (mg/l)
	0-19.99 (mg/l)
	0-199.9 (mg/l)
Input:	3 Wire potentiostatic
Output:	4-20 mA Isolated
Power Requirements:	110 V/60Hz
Display:	4-20 mA
Temperature Compensation:	Manual or Automatic
Operating Temperature:	0-50°C
Mounting:	Wall Mount
Components:	Pressure Switch
	Datalogger
	Manifold
	Sensor Probe
Warranty	5 years

DO-363 Ozone Sensor



This Ozone Sensor has a 0 to 20 ppm range, has 3/4" MNPT connection, can withstand up to 100 PSI, and has an operating temperature range of 0 to 80°C (32 to 176°F).