

450 SCFM Ozone Destruct Unit

Ozone Destruct unit for Large Applications

The ODS-450H is an ozone destruct unit with an integrated heater. This unit can be used where moist air with ozone needs to be 100% free of ozone prior to discharge



Features

- 450-SCFM Flowrate Capacity
- 99.9% Efficient
- 6-in FNPT inlet & outlet
- Stainless Steel Construction
- True Catalytic Reaction
- Integrated Heater
- Order 2 or more and receive a 10% discount
- Order 5 or more and receive a 20% discount

Product ID: **ODS-450H**
Lead Time: **3 weeks**
Price: **\$11,550.00**

Specifications

Maximum Flowrate:	450-SCFM
Destruction Efficiency:	99.96%
Ozone gas type:	handles wet or dry ozone
Integrated Heater:	Yes
Power Required:	120V/60Hz 220 Watts
Pressure Drop:	0.5 PSI at maximum flow rate
Outdoor rated:	Yes
Inlet & Outlet	6-in FNPT
Dimensions	28-in wide x 42-in tall
Weight:	550-lbs
Catalyst Quantity	350-lbs (included)
Warranty:	[link url="http://www.ozonesolutions.com/Limited_Warranty.html"]1 year[/link]

ODS-450H & ODS-3H



This image shows the ODS-450H with the ODS-3H. This shows the overall size difference between these two units.

Top View



Top view of the ODS-450H shows the removable lid. This lid is removable to replace the catalyst inside the ODS-450H easily.